



Green Single Door Gastronorm Cabinets SPI700 & SNI700



2 YEARS
WARRANTY



2-3 DAY
DELIVERY



UK SERVICE
SUPPORT



MADE IN
THE EU



Specifications

Model	Type	Hinge	Capacity Gross / Nett		Temperature	Annual Energy Consumption	Dimensions (mm) Width / Depth / Height			Energy Rating	Refrigerant
SPI700R	Fridge	Right	700 ltrs	461 ltrs	-2°C to +8°C	927 kWh	653	842	2040	D	R290a
SPI700L	Fridge	Left	700 ltrs	461 ltrs	-2°C to +8°C	927 kWh	653	842	2040	D	R290a
SNI700R	Freezer	Right	700 ltrs	461 ltrs	-18°C to -22°C	2179 kWh	653	842	2040	D	R290a
SNI700L	Freezer	Left	700 ltrs	461 ltrs	-18°C to -22°C	2179 kWh	653	842	2040	D	R290a

Key Features

Power supply: 13 amp plug

Castors fitted as standard

Stainless Steel interior and exterior

Shelf dimensions GN2/1

Automatic defrost

Lockable door with replacement gaskets

Intelligent air-circulation system

60mm high-density injected insulation

Green Single Door Gastronorm Cabinets

SPI700 & SNI700



2 YEARS
WARRANTY



2-3 DAY
DELIVERY



UK SERVICE
SUPPORT



MADE IN
THE EU

Efficiency

- “Ventilation Grill” on the front panel keeping the cooling unit system ventilated and running more efficiently.
- Forced draft evaporator with anti-corrosion cover.
- Intelligent Air Circulation system ensures perfect temperature consistency with its innovative airflow design.
- Door switch stops the fan when door is opened to avoid cold air exiting the interior, thus saving energy.
- 60 mm thickness, CFC-free, high-density (40 kg/m³) polyurethane insulation, injected under high pressure

Features

- Fitted with foot pedal and castors. Legs available as an option. Height-adjustable legs available as an option (125mm - 200mm).
- Stamped guides with rounded edges enable more convenient cleaning operations without any difficulties. Placing and adjusting the grids is also easier than ever. Plastic-coated wire grids allow storage of different packaging types and have a maximum loading capacity of up to 40 kg.
- Removable pull-out/ push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties.
- Stamped bottom panel with water drain especially designed to make cleaning operations quicker and easier, optimum for hygiene.
- Rounded edge interiors, easier cleaning operations to reduce potential dirt traps.
- 23 grid level positions for increased loading capacity, with a distance of 55mm between them.
- Automatic evaporation of defrost water. Hot gas from the compressor is used to automatically evaporate defrost water, instead of using a heating element, achieving even less energy consumption and reducing the defrosting time by half.
- Hinged doors with automatic return for a perfect closing that minimize temperature gain. Doors have a 120° dwell position and closes automatically at less than 90°. Door hinges are also reversible allowing the cabinet to be adapted on-site.
- Intuitive digital control allows temperature parameters to be adjusted easily and quickly.
- Luminous start-stop light button.

Contact

Website: www.sterlingpro.co.uk / **Phone:** 01264 560190 / **Email:** sales@sterlingpro.co.uk