SILVERLINK 600



DF4/N - Lincat Silverlink 600 Natural Gas Countertop Single Tank Fryer - 2 Baskets - W 450 mm - 11.3 kW The Silverlink 600 Gas Single Tank
Counter Top Fryer delivers 25kg of
chips per hour, while it also features a
twin basket operation which gives you
the flexibility of cooking different foods
or loads simultaneously.

- Single tank fryer with twin basket operation giving you the flexibility to cook different foods or loads simultaneously, delivering 25kg of chips per hour
- Front mounted controls for safety
- Thermostatically controlled to give accurate cooking temperatures throughout cooking. Flame failure device and top temperature cut out ensures safe operation.
- Cool zone collects cooking debris gives cleaner cooking results and saves money by prolonging the life of the oil

- Piezo ignition for easy lighting
- Heavy duty nickel plated baskets for the most demanding of operations
- Front drain off tap for easy removal of cooking oil

Specifications

Net Weight Kg

30.9

Summary		Power and Performance	
Brand	Lincat	BTU per Hour	38,555
Range	Silverlink 600	Total Power kW	11.3
Power Type	Gas	Temperature Range °C	110-190
Gas Type	Natural Gas	Temperature Control	Mechanical
Unit Type	Counter-top		
Available in UK Only	No		
UK Warranty	2 Years Parts and Labour Warranty		
Export Warranty	Contact your local dealer		
GTIN	5056105104605		
Key Specifications		Capacity	
Number of Baskets	2	Product Output per Hour	16kg chips - 12mm [frozen], 25kg chips
Number of Tanks	1		12mm [chi
Gravity Filtration	No	Capacity Litres	8.0
Pumped Filtration	No		
Drain Location	Front-mounted		
Weights and Dimensions		Supply Connections	
Unit Height (External) mm	415	Requires Installation	Yes
Unit Width (External) mm	450	Requires Electrical Supply	No
Unit Depth (External) mm	654	Gas Connection BSP	1/2"

Gas Consumption at full rate Natural

Total heat input at full rate Natural

Total heat input at full rate Natural

Gas Pressure Natural mbar

m³ per Hour

1.08

16.2

11.3

38,600





Shipping

 Packed Weight Kg
 33.99

 Packed Height cm
 63.5

 Packed Width cm
 70

 Packed Depth cm
 55

Available Accessories

CH01 Caterflex Hose 1/2" - 1 Metre - for use with units up to 66,000 BTU


CH02 Caterflex Hose 1/2" - 1.5 Metre - for use with units up to 56,000 BTU


CN4 Lincat Silverlink 600 Free-standing Ambient Open-Top Pedestal without Doors - W 450 mm


DC01 DONUT CONV KIT DF4/GAS

SLS4 Lincat Silverlink 600 Free-standing Floor Stand - for units W 450 mm

Technical Picture













Lincat Limited

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

Company No: 2175448

A member company of

Customer Care

Tel: +44 1522 875500

Email: care@lincat.co.uk

Export Customers

Tel: +44 1522 875536

Email: export@lincat.co.uk

Opening Hours

Monday - Friday:

8.30am - 5pm

