



## LCSH110I - Lincat CombiSlim 1.10 Electric Counter-top Combi Oven - Injection with Hoodini - W 513 mm - 12.7 + 2.2 kW

Choose CombiSlim with a Ventless Hoodini solution, to gain maximum flexibility using minimum space.

- ✓ Ideal for where venting to the atmosphere is impractical, allow the setup of a cooking station in previously unsuitable areas of a building
- ✓ Utilise non-traditional spaces in the kitchen, front of house or back bar to diversify operations
- ✓ Gain maximum flexibility using minimum space with CombiSlim ovens. These combi ovens measure only 51.4 cm in width and fit into all professional kitchens
- ✓ CombiSlim ovens are ideal for small-scale food production in take-away shops, cafés, etc
- ✓ Intuitive touch display SmartTouch® for programming
- ✓ 1/1GN compatible
- ✓ Steam injection, with CombiSmart® humidity control
- ✓ Ability to create cooking programmes with up to 15 steps
- ✓ Rack timer allowing accurate cooking times for different items on different shelves
- ✓ Two-step safety handle

### Specifications

#### Summary

Brand	Lincat
Range	Lincat Combi Ovens
Series	CombiSlim
Power Type	Electric
Unit Type	Counter-top
Available in UK Only	Yes
UK Warranty	2 Years Parts and Labour Warranty
GTIN	5056105121787

#### Power and Performance

Total Power kW	12.7 + 2.2
Temperature Range °C	30-300
IP Rating	IPX5
Temperature Control	Electronic
Oven Rating kW	Steam connection = N/A; Hot air connection = 12.7

#### Key Specifications

WRAS Approved	Yes
Type of Lighting	Halogen
Number of Grids included	0

#### Capacity

Gastronorm Capacity	10 x GN1/1 (20mm deep)
Portions per Day	90

#### Weights and Dimensions

Unit Height (External) mm	1369
Unit Width (External) mm	514
Unit Depth (External) mm	962
Height (Internal) mm	550
Width (Internal) mm	400
Depth (Internal) mm	630
Net Weight Kg	129

#### Supply Connections

Requires Installation	Yes
Requires Electrical Supply	Yes
UK 3 Pin Plug	Yes
Requires Hardwiring	Yes
Electrical Supply Rating Watts	12,700 + 2,200
Single Phase Amps	9
Single Phase Voltage	230
Three Phase Amps	L1=21.0; L2=21.0; L3=21.0
Three Phase Voltage	400
Water Connection Pressure Bar	2.5-6
Drain Connection	DN 40 mm
Water Connection	3/4"

## Shipping

<b>Packed Weight Kg</b>	141.9
<b>Packed Height cm</b>	143.8
<b>Packed Width cm</b>	80
<b>Packed Depth cm</b>	120

## Available Accessories

<b>LCA3003</b>	Lincat Combi Oven Imperial Non-stick Container - GN1/1 (325 x 530 mm) - 20 mm deep
<b>LCA3005</b>	Lincat Combi Oven Imperial Non-stick Container - GN1/1 (325 x 530 mm) - 40 mm deep
<b>LCA3007</b>	Lincat Combi Oven Imperial Non-stick Container - GN1/1 (325 x 530 mm) - 60 mm deep
<b>LCA3009</b>	Lincat Combi Oven Imperial Pizza and Grilling Sheet - GN1/1 (325 x 530 mm)
<b>LCA3011</b>	Lincat Combi Oven Imperial Grilling Grid - GN1/1 (325 x 530 mm)
<b>LCA3012</b>	Lincat Combi Oven Imperial Potato Grid - GN1/1 (325 x 530 mm) - 28 Potato Capacity
<b>LCA3013</b>	Lincat Combi Oven Imperial Multi-tray - 8 Moulds - GN1/1 (325 x 530 mm)
<b>LCA3015</b>	Lincat Combi Oven Non-stick Aluminium Baking Sheet - GN1/1 (325 x 530 mm)
<b>LCA3017</b>	Lincat Combi Oven Non-stick Perforated Aluminium Baking Sheet - GN1/1 (325 x 530 mm)
<b>LCA3019</b>	Lincat Combi Oven Silicone Baking Mat - GN1/1 (325 x 530 mm)
<b>LCA3021</b>	Lincat Combi Oven Steamfry Basket - GN1/1 (325 x 530 mm)
<b>LCA3023</b>	Lincat Combi Oven Rack for Spare Ribs - GN1/1 (325 x 530 mm)
<b>LCA3024</b>	Lincat Combi Oven Chicken Grid - GN1/2 (325 x 265 mm) - 4 Chicken Capacity
<b>LCA3025</b>	Lincat Combi Oven Chicken Grid - GN1/1 (325 x 530 mm) - 8 Chicken Capacity
<b>LCA4001</b>	Lincat Combi Oven Software Key - Quick Select Recipes (QSR)
<b>LCA6006</b>	Lincat Combi Oven Static Stand for CombiSlim - Open Stand
<b>LCA6007</b>	Support Rail Cassette for LCA6006 Stand for CombiSlim - 10 Support Rails
<b>LCC1001</b>	Hydro Shield 3600 (L) Water Filter Cartridge - Recommended for CombiSlim and Visual Cooking 1.06/1.10
<b>LCC1002</b>	Hydro Shield 6000 (XL) Water Filter Cartridge - Recommended for Visual Cooking 1.20/2.06/2.10/2.20 and all Combi Ovens in hard water areas
<b>LCC1003</b>	Hydro Shield 3600 (L) Water Filter Kit - Including Filter, Filter Head and Hose - Recommended for CombiSlim and Visual Cooking 1.06/1.10
<b>LCC1004</b>	Hydro Shield 6000 (XL) Water Filter Kit - Including Filter, Filter Head and Hose - Recommended for 1.20/2.06/2.10/2.20 + all Ovens in hard water areas
<b>LCC2003</b>	Lincat Protect Intense Detergent - 2 x 5l
<b>LCC2005</b>	Lincat Protect Cleaning Package - 6 x 5l Intense Detergent and 2 x 5l Rinse Aid
<b>LCC2006</b>	Lincat Protect Rinse Aid - 2 x 5l
<b>OCG6111</b>	1/1 GN GRID-S/STEEL - P/NO. GN1/1-1D6 20D3



### Lincat Limited

Whisby Road,  
Lincoln, LN6 3QZ,  
United Kingdom

**Company No:** 2175448

A member company of



### Customer Care

**Tel:** +44 1522 875500  
**Email:** care@lincat.co.uk

### Export Customers

**Tel:** +44 1522 875536  
**Email:** export@lincat.co.uk

### Opening Hours

**Monday – Friday:**  
8.30am – 5pm