



P8B3 - Lincat Panther 800 Series Free-standing Hot Cupboard - Bain Marie Top - 3GN - W 1205 mm - 2.8 kW Helping to cater in demanding environments such as cafeterias, canteens and restaurants, the Panther 800 Series Hot Cupboard / Bain Marie is an effective way of holding food at the desired temperature, and is perfect for holding carvery and breakfast items either for self service or for back service.

- Helping to cater in demanding environments such as cafeterias, canteens and restaurants
- Fan assisted hot cupboard provides even heat distribution, fast heat up and recovery times, and lower energy usage. Four shelf positions allow adjustment to meet individual needs.
- Fully 1/1 GN compatible hot cupboard for operational efficiency. Units available to take 3 x 1/1 GN containers up to 150mm deep.
- Thermostatically controlled bain marie top can be operated with wet or dry heat. Accurate digital electronic control of the hot cupboard temperature, adjustable between 20 and 99 °C, ensures compliance with food hygiene regulations
- Double skinned construction provides efficient heat retention and a cool to touch exterior - safe and energy efficient. Removable doors and shelves allow access to the fully stainless steel interior for easy cleaning
- Supplied with two heavy duty multi-section chrome plated rod shelves capable of taking the heaviest loads
- Drain tap located inside the hot cupboard allows fast and easy draining

## **Specifications**

Summary		Power and Performance	
Brand	Lincat	Total Power kW	2.80
Range	Panther	Temperature Range °C	20-99
Series	800 Series	IP Rating	IP24
Power Type	Electric	Temperature Control	Top: Mechanical; Bottom: Electronic
Unit Type	Free-standing		
Available in UK Only	No		
UK Warranty	2 Years Parts and Labour Warranty		
Export Warranty	Contact your local dealer		
GTIN	5056105103479		

#### **Drain Location Gastronorm Capacity** 3 x GN1/1 Right side interior mounted **Number of Shelves included** 2 **Plate Capacity** 316 **Number of Shelf Positions** Pot Type Gastronorm Type of Heat Wet/Dry **Heated Base Heated Gantry** Static or Mobile Mobile





Weights and Dimensions		Supply Connections	
Unit Height (External) mm	912	Requires Installation	No
Unit Width (External) mm	1205	Requires Electrical Supply	Yes
Unit Depth (External) mm	850	UK 3 Pin Plug	Yes
Height (Internal) mm	432	Requires Hardwiring	No
Width (Internal) mm	1,020	<b>Electrical Supply Rating Watts</b>	2,800
Depth (Internal) mm	512	Single Phase Amps	12.4
Shelf Dimensions Width mm	967	Single Phase Voltage	230
Shelf Dimensions Depth mm	512		
Net Weight Kg	102.5		
Shipping			
Packed Weight Kg	112.75		
Packed Height cm	110		
Packed Width cm	123		
Packed Depth cm	90		

	Ava	ailab	ole C	)pti	ions
--	-----	-------	-------	------	------

_		
Overs	helf o	r Gantrv

PG3A PG3A - Ambient Gantry
PG3H PG3H - Heated Gantry
PS3A1 PS3A1 - 1 Ambient Overshelf
PS3A2 PS3A2 - 2 Ambient Overshelves
PS3A3 PS3A3 - 3 Ambient Overshelves
PS3H1 PS3H1 - 1 Heated Overshelf
PS3H2 PS3H2 - 2 Heated Overshelves

PS3H3 - 3 Heated Overshelves

Door Locks

PS3H3

PDL3 - Lockable Door

**Corner Guards** 

PCG - Corner Guards [Set of Four]

Trayslides

PTS3 - Tray Slide

Legs/Castors


**PLK** - Legs[non chargeable]


Avai	lable	Access	sories


CP16	CP16 - CARVERY PAD[1/1 GASTRONORM SIZE]
PGK4	PGK4 - GASTRONORM PACK
PGK5	PGK5 - GASTRONORM PACK
PGK6	PGK6 - GASTRONORM PACK
PGK7	PGK7 - GASTRONORM PACK
PHTC	PHTC - CERAMIC INSERT [1/1 GASTRONORM SIZE]
PHTG	PHTG-GLASS INSERT[1/1 GASTRONORM SIZE]
PLK/S	PLK/S - LEG KIT [FOR CONVERSION IN THE FIELD]
PPB8	PPB8 - ADDITIONAL PUSHBAR



# Technical Picture









#### **Lincat Limited**

Whisby Road,

Lincoln, LN6 3QZ,

United Kingdom

**Company No:** 2175448

A member company of

#### **Customer Care**

**Tel:** +44 1522 875500

Email: care@lincat.co.uk

#### **Export Customers**

**Tel:** +44 1522 875536

Email: export@lincat.co.uk

### **Opening Hours**

Monday - Friday:

8.30am - 5pm