



# Product Code: **FMPRO1200RF 19-147**

## **1200mm multideck with Roller shutters**

---



### Features & Benefits

---

- Five display levels maximising capacity
- Energy saving LED lighting is brighter, lasts longer and saves you money
- Additional shelf depth (450mm) delivers increased volume compared to competitor cabinets
- Supplied on roller castors as standard for ease of positioning
- Add 20mm to depth for spacer if product is to be wall-sited (required for air circulation - detachable if not wall-sited)
- 1x top mounted full length LED. On average these last 10x longer than fluorescent lighting and emit a fraction of the heat output.
- Robust lockable security roller shutter with full solid end panels
- Fully removable shelves and supports for ease of cleaning.
- Removable front cover and slide out condensing unit allows easy access for service, minimising down time. Also our After Sales Support is there when you need us: 2 years parts and labour warranty as standard.

Refrigeration		Electrical & Service Data		Product Extras	
R290 - Energy Efficient	Standard	230/50/1	Standard	Additional S/S shelf and support brackets	Option
Integral Refrigeration System	Standard	Fuse Required (A)	10		
Specification		Finish		Front wire baskets for additional storage	Option
M2 Temp +2/+4°C	Standard	304 s/s ext & int	Standard		
Width (mm)	1195				
Depth (mm)	775				
Height (mm)	2040				
Unpacked weight (Kgs)	190				
Packed weight (Kgs)	211.14				

## Footnotes

- Allow 60mm spacer if product is wall-sited (required for air circulation). Spacers are detachable if product is not to be wall-sited
- Performance complies with M2 classification as prescribed in EN23953-2:2005. M2 refers to product temperatures of no greater than +7°C and no lower than -1°C when loaded in accordance with the standard and recorded under test conditions.



The Refrigeration Experts

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU  
+44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.