

PROMOPage Catalog : **1091**Page Promo : **71**

Professional gravity-feed slicer Ø 300 mm (12")

300/BS

Lame diam. 300 mm

Descriptions

mm (L x W x H)	610 x 535 x 510
kW	0.21
Weight	26 kg
Voltage	230/1N 50HZ
Hp	0.29
Volume m3	0.27 m ³

Product details

- Compact, but with a large cutting capacity, realized in anodized and polished aluminum alloy.
- Sanitary polished and anodized aluminium alloy, hardened, chromed stainless blade, permanent tapered blade ring guard and interlocked blade guard (100% safe).
- Reinforced gauge plate, max. cutting capacity 250xh185 (Ø 210 mm) slice thickness 0-13 mm.
- Carriage sliding on stainless bearings for an easy and quiet operation, a plexiglass hand guard comes standard.
- Stainless steel screws and deflector.
- Dual-action built-in sharpener.
- Low-voltage controls 24 V, protection class IP 44, keypad enclosure, NVR (No-Voltage Release) to prevent accidental restart after power failure.
- Adjustable feet.
- The equipment is manufactured following the (CE) standards in force

Important: easy and safe cleaning thanks to:

- 1°) Wide gap between blade and body.
- 2°) Removable carriage system with gauge plate protecting blade edge at default slice thickness setting below "0".
- 3°) Removable blade guard.
- 4°) Permanent tapered blade ring guard.