



Blast Chillers

SP20BC / SP40BC / SP60BC

1 Year Parts & Labour Warranty

2-3 Working Days Delivery

UK Service Support



The Sterling Pro Cobus blast chiller range is the best machine for chilling and freezing hot food quickly. Capable of chilling or freezing food from 100°C, it enables the safe storage of freshly cooked food for serving at a later date. It is manufactured from the highest quality AISI304 stainless steel meaning it is extremely robust and easy to keep hygienically clean.

Model	Grids (Not included)	Chill Capacity	Freeze Capacity	Climate Class	Dimensions (mm)		
SP20BC	5	20kg in 90 minutes	15kg in 270 minutes	4	W800	D800	H930
SP40BC	10	40kg in 90 minutes	28kg in 270 minutes	4	W800	D800	H1515
SP60BC	13	60kg in 90 minutes	38kg in 270 minutes	4	W800	D800	H1763



Blast Chillers

SP20BC / SP40BC / SP60BC



Range Specifications			
	SP20BC 5 Grid Blast Chiller	SP40BC 10 Grid Blast Chiller	SP60BC 13 Grid Blast Chiller
GTIN Code	5060750321867	5060750321874	5060750321881
Dimensions	W800 x D800 x H930mm	W800 x D800 x H1515mm	W800 x D800 x H1763mm
Internal Dimensions	W670 x D660 x H380mm	W670 x D660 x H732mm	W670 x D660 x H958mm
Packed Dimensions	W860 x D860 x H1050mm	W860 x D860 x H1560mm	W860 x D860 x H1830mm
Grids	5 (grids not included)	10 (grids not included)	13 (grids not included)
Chill Capacity	20kg in 90 minutes	40kg in 90 minutes	60kg in 90 minutes
Freeze Capacity	15kg in 270 minutes	28kg 15kg in 270 minutes	38kg 15kg in 270 minutes
Pans / Shelves	Fits GN1/1 pan / 600x400 shelves	Fits GN1/1 pan / 600x400 shelves	Fits GN1/1 pan / 600x400 shelves
Exterior Finish	AISI304 Stainless Steel	AISI304 Stainless Steel	AISI304 Stainless Steel
Interior Finish	AISI304 Stainless Steel	AISI304 Stainless Steel	AISI304 Stainless Steel
Max Ambient	32°C	32°C	32°C
Refrigerant	R290	R290	R290
Insulation Thickness	65mm	65mm	65mm
Nett Weight	108kg	129kg	170kg
Energy Rating	N/A	N/A	N/A
Climate Class	4	4	4
Power Supply	13 amp single phase plug	13 amp single phase plug	13 amp single phase plug
Voltage	220-240V/50HZ	220-240V/50HZ	220-240V/50HZ
Digital Display	Yes	Yes	Yes
Cooling System	Ventilated	Ventilated	Ventilated
Defrost Type	Automatic	Automatic	Automatic
Reversible Doors	No	No	No
Lighting	No	No	No
Lockable	No	No	No
Castors	No	No	No
Frost Free	No	No	No
Charging Volume	150g	150g	150g
Compressor Code	SC18CNX.2	SC21CNX.2	NT2210U
Compressor Brand	SECOP	SECOP	SECOP