

Product specification



HR360G: 360 Ltr Undercounter Cabinet Refrigerator

13-251

Glass door undercounter refrigerator cabinet (with light)

Features and benefits

- Front breathing refrigeration system makes this model suitable for use in enclosed areas
- Integrated door lock for added security
- High quality magnetic door gasket
- Easy to use microprocessor control with digital display for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- Supplied with glass door for optimum visibility of stored product
- Supplied on roller castors as standard for ease of movement and positioning
- Operates in ambient temperatures of up to 25°C (ISO Climate Class 3)

Technical

Refrigerant	R290
Temperature	Refrigerator +3/+5°C
Electrical supply	230/50/1
Fuse rating (A)	10
Current (A)	2
Power (W)	220
Refrigerant mass (g)	123

Build

Finish ext/int	S/S & Alu
Number of sections	2
Section configuration	Left hinge,Right hinge
System	Integral

Dimensions

Height (mm)	824
Width (mm)	1217
Depth (mm)	755
Gross volume (ltr)	360
Net volume (Itr)	188.9
Leg type	Roller castors rear, levelling bolts front
Gross weight (kg)	90.5
Net weight (kg)	90.5

Energy

Climate Class	3
Energy grade	В
EEI	10.4
AEC (kWh)	456
Energy consumption (kWh/24hr)	1.2
GWP	3
Min - max temperature (°C)	-1/5

Footnotes

• External cabinet depth excludes 25mm door handle

We use cookies to ensure you get the best experience on our website. More information.

Accept all

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | <u>www.fosterrefrigerator.com</u>

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.