

# **Product specification**



### FMPRO900NG: 446 Ltr Pro Multideck

19-141

Pro 900mm multideck with fully frameless doors

#### Features and benefits

- Extra wide glass end panels increase display visibility
- Energy saving retracting 'soft closing mechanism' nightblind
- Removable front cover and slide out condensing unit allows easy access for service, minimising down time
- Energy saving acrylic doors prevent the escape of cold air whilst allowing clear view of stored merchandise
- · High impact energy saving LED lighting is brighter, lasts longer and saves money in energy costs
- 2 vertical side mounted full length LED lights last on average 10 x longer than fluorescent lighting and emit a fraction of the heat output
- The Foster Pro Multideck's five display levels maximise capacity and reduce the need for frequent re-stocking
- Additional shelf depth (450mm) delivers increased volume compared to competitor cabinets
- Fully removable shelves and supports for ease of cleaning
- Supplied on roller castors as standard for ease of movement and positioning

We use cookies to ensure you get the best experience on our website.

More information.

Accept all Decline all

#### **Technical**

Refrigerant R290

**Temperature** Display -1/+7°C

Electrical supply

230/50/1

supply

Fuse rating 10

(A)

Current (A)

5 1050

Power (W)
Refrigerant

150

mass (g)

810

Thermal heat rejection (kW)

#### Build

Finish ext/int 304 S/S & 304 S/S

Section configuration

System Integral

#### **Dimensions**

**Height (mm)** 1960

**Width (mm)** 895

**Depth (mm)** 735

Gross volume 446

(ltr)

**Leg type** Roller castors

Gross weight 183.5

(kg)

Net weight 175

(kg)

## Energy

Climate Class 3

**Energy grade** C

**EEI** 29.3

**AEC (kWh)** 3126

Energy 9.2 consumption (kWh/24hr)

**GWP** 3

Min - max -1/7 temperature

(°C)

#### Footnotes

- Allow 60mm spacer if product is wall-sited (required for air circulation). Spacers are detachable if product is not
  to be wall-sited
- Performance complies with M2 classification as prescribed in EN23953-2:2005. M2 refers to product temperatures of no greater than +7°C and no lower than -1°C when loaded in accordance with the standard and recorded under test conditions.

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.

We use cookies to ensure you get the best experience on our website.

More information.