

Product specification



EP700L: 600 Ltr Cabinet Freezer

41-106

Single door freezer cabinet

Features and benefits

- Fitted with our new and improved +stayclear condenser which helps increase product life and reduce energy consumption, +stayclear helps your low energy fridge stay a low energy fridge. Now fitted across the cabinet and counter range as standard
- Foster Shield provides advanced temperature control and hygienic design, protecting from the dangers of unsafe food storage. With air distribution optimised by CFD design technology, efficient operation is assured, even when shelves are fully loaded
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 the gold standard in performance stainless steel – meaning the heaviest usage touchpoints on the product are covered
- Market leading usable capacity, now supplied with 4 shelves as standard making your money go further – holds more than a conventional fridge
- Operates efficiently in ambient temperatures of up to 43°C

We use cookies to ensure you get the best experience on our website.

More information.

Accept all

Decline all

Technical

Refrigerant R290

Temperature Freezer -18/-21°C

Electrical supply

230/50/1

Fuse rating 10

(A)

Current (A) 1.2

Power (W) 270

Refrigerant mass (g)

80

Thermal heat

280

rejection (kW)

Build

Standard Cabinet type

Finish ext/int S/S & Alu

Number of sections

Section Right hinge

configuration

System Integral

Dimensions

Height (mm) 2080

Width (mm) 700

Depth (mm) 855

Gross volume 600

(ltr)

Net volume

(ltr)

479.9

Leg type

Braked castors

GN size

Gross weight

(kg)

130.5

121.5

Net weight

(kg)

2/1

Energy

Climate Class

Energy grade

30.25 EEI

AEC (kWh) 1161

3.18 Energy consumption

(kWh/24hr)

GWP 3

We use cookies to ensure you get the best experience on our website.

Footnotes

- 150mm castors are not available if product is supplied less condensing unit
- Adequate airflow and service space must be kept above the top of cabinet: 100mm
- Depth with door open is 1500mm

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | <u>www.fosterrefrigerator.com</u>

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.

We use cookies to ensure you get the best experience on our website.

More information.