

# **Product specification**



HR200G: 200 Ltr Undercounter Cabinet Refrigerator

13-114

Glass door undercounter refrigerator cabinet (no light)

### Features and benefits

- Front breathing refrigeration system makes this model suitable for use in enclosed areas
- High quality magnetic door gasket
- Easy to use microprocessor control with digital display for easy visual reference
- Stainless steel exterior as standard with aluminium interior
- Supplied with glass door for optimum visibilty of stored product
- Supplied on roller castors as standard for ease of movement and positioning
- Operates in ambient temperatures of up to 25°C (ISO Climate Class 3)

Build

Technical

Refrigerant	R290
Temperature	Refrigerator +3/+5°C
Electrical supply	230/50/1
Fuse rating (A)	10
Current (A)	1.2
Power (W)	225
Refrigerant mass (g)	116
Thermal heat rejection (W)	250

Finish ext/int	S/S & Alu
Number of sections	1
Section configuration	Right hinge
System	Integral

Dimensions		
Height (mm)	824	
Width (mm)	684	
Depth (mm)	755	
Gross volume (ltr)	200	
Net volume (ltr)	98	
Leg type	Roller castors rear, levelling bolts front	
Gross weight (kg)	62.5	
Net weight (kg)	56	

## Energy **Climate Class** 3 **Energy grade** Α EEI 9 AEC (kWh) 390 **GWP** 3 Min - max -1/5 temperature (°C) **Energy** 1.07 consumption (kWh/24hr)

# **Options**

#### **Drawer/Door material** Stainless steel

#### Footnotes

- External cabinet depth excludes 25mm door handle
- For ventilation, ensure that 50mm clearance is allowed above and around the cabinet

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.