

Product specification



EP700SH: 550 Ltr Cabinet Refrigerator

41-763

Single door low height refrigerator cabinet

Features and benefits

- Suitable for low ceiling height applications
- Lower energy consumption & 33% energy saving vs previous model
- All the benefits of the standard G3, but this product can fit through a standard (1960 x 760) doorway without tilting
- With this model's smaller footprint, it is a great option where available kitchen space is an issue
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 – the gold standard in performance stainless steel – meaning the heaviest usage touchpoints on the product are covered
- Greater usable internal storage capacity an increase of 28 litres over the previous model
- Fully GN 2/1 shelving compatible
- Operates efficiently in ambient temperatures of up to 43°C

Technical

Refrigerant R290 **Temperature** Refrigerator +1/+4°C 230/50/1 **Electrical** supply Fuse rating (A) 10 Current (A) 0.6 Power (W) 140 Refrigerant 80 mass (g) Thermal heat 140 rejection (W)

Build

Cabinet type	Short
Finish ext/int	S/S & Alu
Number of sections	1
Section configuration	Left hinge
System	Integral

Dimensions

Height (mm)	1955
Width (mm)	700
Depth (mm)	855
Gross volume (ltr)	550
Net volume (ltr)	439.6
Leg type	Braked castors
GN size	2/1
Gross weight (kg)	158
Net weight	149

Energy

5
Α
24.01
319.6
3
0.88

Options

Drawer/Door material 304 Stainless steel

Hinge Right

Electrical supply 220/60/1

Footnotes

• Requires 100mm free space above product

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.